Amendment to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (original) A door lock control system, comprising:
 - a door mounted in a door frame;
 - a door lock associated with the door to lock and unlock the door;
 - control means to lock and unlock the door lock; and,
- a vibration sensor associated with the control means, the control means causing the door lock to be unlocked when a vibration above a certain level is sensed by the vibration sensor.
- (original) The door lock control system of claim 1, and further comprising: the door lock is a magnetic lock.
- 3. (original) The door lock control system of claim 1, and further comprising:
 the vibration sensed by the vibration sensor is an earthquake or a bomb explosion.
- 4. (currently amended) The door lock control system of claim 1, and further comprising:

the vibration sensor includes a permanent magnetic magnet connected to a pendulum, as magnetic contact positioned near the permanent magnet, and a relay switch.

- 5. (original) The door lock control system of claim 1, and further comprising:
 - the control means to lock and unlock the door lock further comprises:
 - a low voltage DC power source;
 - a backup battery:

a relay switch; and,

the vibration sensor.

6. (currently amended) The door lock control system of claim 5, and further comprising:

the low voltage DC power source, the backup battery, the relay switch and the vibration sensor are all contained within a control box.

7. (currently amended) The door lock control system of claim 6, and further comprising:

the control box is mounted at a location remote from small non-threatening vibrations caused by movement of the door.

- 8. (original) The door lock control system of claim 6, and further comprising:
 the control box is mounted to a rigid wall or column remote from the door.
- (withdrawn) A method of controlling a lock on a door, comprising the steps of: maintaining a door in a locked state; monitoring for vibrations near the door;

determining if the monitored vibration is above a certain level; and, unlocking the door if the vibration is above the certain level.

10. (withdrawn) The method of controlling a lock on a door of claim 9, and further comprising the steps step of:

the step of monitoring for vibrations includes monitoring for an earthquake or a bomb explosion.

11. (withdrawn) The method of controlling a lock on a door of claim 9, and further comprising the steps step of:

the step of determining if the monitored vibration is above a certain level includes the step of determining if the vibration is above 0.1 g.

- 12. (withdrawn) A control box, comprising:
 - a box;
 - a door hinged to the box;
 - a DC power supply mounted in the box;
 - a backup battery mounted in the box;
 - a terminal and fuse board mounted in the box; and,
 - a vibration sensor mounted in the box.
- 13. (withdrawn) The control box of claim 12, and further comprising: the DC power supply is a low voltage power supply.
- 14-24. (canceled)
- 25. (previously presented) The door lock control system of claim 1, further comprising:
 a means for delaying the unlocking of a door by a predetermined time, wherein
 the vibration sensor detects the vibration above the certain level, the control means
 unlocks the door and overrides the means for delaying the unlocking of the door.